(19) World Intellectual Property Organization International Bureau



TEGER IN PERIOR HERE ELECTRICATE ENGLISH HERE ELECTRICATE ELECTRICATE HERE ELECTRICATE IN THE FOLLOW IN THE FOLLOW

(43) International Publication Date 6 May 2005 (06.05.2005)

(10) International Publication Number WO 2005/040693 A2

(51) International Patent Classification7;

F24F 5/00

English

- (21) International Application Number:
 - PCT/EP2004/011833
- (22) International Filing Date: 18 October 2004 (18.10.2004)
- English (25) Filing Language:
- (26) Publication Language:
- (30) Priority Data: 17 October 2003 (17.10.2003) GB 0324348
- (71) Applicant (for all designated States except US): OXY-CELL HOLDING BV [NL/NL]; Kaagstraat 17-19, 8102 GZ Raalte (NL).
- (72) Inventor: and
- (75) Inventor/Applicant (for US only): REINDERS, Johannes, Antonius, Maria [NL/NL]; Oude Warkenseweg 1. NL-7231 Warnsveld (NL).
- (74) Agent: CLARKSON, Paul; Howrey Simon Arnold & White, Citypoint, One Ropemaker Street, London EC2Y 9HS (GB).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: HEAT EXCHANGE LAMINATE



liquid retaining layer, can be imparted to the heat exchange laminate prior to forming. The laminate may then be conveniently formed into any desired shape by known manufacturing procedures for incorporation into a heat exchanger. The laminate may be used to cool a first fluid by evaporation of a liquid into a second fluid operating at or near its saturation point.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.